Desks

General Specifications

Table tops: 1-1/4" thick, three-ply 45# particleboard construction with a .050" high pressure laminate top surface and a .030" phenolic backer.

Corners for rectilinear tops: square corners on banded tops have a 1/8" radius.

Leg and Frame Assembly: Welded end frames consist of 1-1/2" square, 14 gauge steel tubing. End frames are connected to (2) 1-1/2" square steel tube spanners using 1/4-20 machine bolts. 3/4" diameter X 3/4"H spacers are placed between the top and the understructure. Frame assembly attaches to worksurface using 1/4-20 machine bolts. Legs are fitted with adjustable glides.

Modesty Panel: Panels are $\frac{3}{1}$ thick, three ply $\frac{45}{1}$ particle board construction with .050" high pressure laminate on both faces. Edge is 3mm PVC or Wood with a $\frac{1}{8}$ radius top and bottom. Modesty panels connects to one horizontal spanner via $\frac{1}{1}$ -20 bolts and inserts.

Finish: Standard powder coat on all metal parts is black; other colors may be specified. See mediatechnologies® Finish and Color Guide for choices.







			GTX Desk	
Model Number	Description	Wgt	List Price	
			VC Edges	
GD-C3060-29	GTX Desk, 30" x 60" x 29"H	120	\$1,579	
GD-C3072-29	GTX Desk, 30" x 72" x 29"H	131	\$1,715	

Required to order: Model # including options if applicable

- HPL selection
- PVC selection
- powder coat selection

