

ROCKY

Benches



RB-1860A

18"D X 60"W X 18"H

ROCKY



RB-1860C



RB-1860A

ROCKY BENCH

- Wood seat is 1-3/8" thick solid hardwood.
- Cozy, upholstered seat cushion is 1.5" thick high-density upholstery foam.
- Available in 48" and 60" widths.
- Sturdy, powder coated steel leg frames with nylon-base leveling glides.

To Order, Choose Finish Selections & Options

Base: Choose from our selection of powder coats.

Seat: Choose between Oak or Maple in many standard finishes.

Seat Cushion: Choose fabric for seat cushion, if applicable.

See **MTContracts'** Finish selections at
<https://www.mtcontract.com/resources/finishes>
View our fabric choices at
<https://www.mtcontract.com/resources/fabrics>

ROCKY STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
RB-1848_	18	48	18
RB-1860_	18	60	18

General Specifications

Frame: 14 gauge 1" x 2" rectangular steel tubing leg frame assemblies are fully welded to a 1/4" thick steel mounting plate. Mounting plate is fastened to bench with 1/4"-20 bolts. Legs are fitted with threaded inserts and receive 5/16-18 adjustable 1-7/8" Dia. black nylon adjustable glides.

Cushioned Seat: 1-1/2" thick high density upholstery foam with a 1/2" thick backer board attaches to a 1" thick hardwood veneer core with 5/8" x 1-3/4"

banding with beveled top edge and 1/8" radiused corners. Cushioned tops are attached with wood screws.

Wood Seat: 1-3/8" thick solid hardwood, is made up of glued up strips of wood no less than 4" (with no more than two per top) or greater than 6" in width. 1/8" radius on all corners and edges.



892 Industrial Park Drive
Shelby, MI 49455
P: 231.861.2194 | F: 231.861.6678
www.mtcontract.com
sales@mediatechnologies.com

cs-rocky-180822

PURE MICHIGAN®