

# PORTER

---

## Desks



PDCT22-C3060-ADJ

30"D X 60"W X 27-1/4"-45"H

 mt contract

# PORTER DESK



PDCT22-C3060-ADJ



PDCT22-C3060-ADJ  
Shown with optional Grommets  
and Keyboard and Mouse Tray.



Hand Crank Detail

## PORTER ADJUSTABLE HEIGHT DESK

- Adjustable height teacher desk.
- 1-1/4" thick high pressure laminate work surface with 3mm PVC edges.
- Desk is manually adjustable in height from 27-1/4" to 45" with hand crank.
- Desk base is powder coated steel\* and is fitted with nylon leveling glides.
- 11-3/4"H high-pressure laminate modesty panel.
- Optional 2" locking casters (4).

### To Order, Choose Finish Selections & Options

**Base:** \*Available powder coats are: Silver 809, Black 912, Lime Green 502, Capri Blue 701 or Navy 5003.

**Work Surface and Modesty Panel:** Choose your high pressure laminate and PVC Edgeband colors.

See **MTContract's** finish choices at:  
<https://www.mtcontract.com/resources/finishes>

### EDGE TYPE



**C**  
3mm  
PVC

### OPTIONS



80mm  
Grommet



AGC  
Cable Grip



AWM  
Cable Channel



AAKT001  
Keyboard Tray



MCD1817  
Pencil Drawer



AAKT003  
Keyboard and  
Mouse Tray



Locking  
Casters

**Note:** Optional casters add 2" to the starting height of the adjustment range.

### PORTER DESK STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
PDCT22-C3060	30	60	27-1/4"-45"
PDCT22-C3072	30	72	27-1/4"-45"

### General Specifications

**Table Top:** Table tops are 1-1/4" thick, three-ply 45# particleboard construction with .050" high-pressure laminate top surface, a .030" phenolic backer and a 3mm PVC edgeband. Square corners on banded tops have a 1/8" radius.

**Steel Crank-End Base:** Three-stage column is 2mm square powder coated steel tube. Outer tube is 2.76". Middle tube is 2.48". Inner tube is 2.20". Column is offset 3" from center of foot. Foot is 3" x 1/2" machined powder coated steel bar. Each foot is fitted with (2) 5/16"-18 x 1/2" long threaded stem levelers with black nylon base. Top of column fitted with 8" x 8" x 1/4" powder coated steel mounting plate. Mounting plate and foot attached to column with set of (4) 8mm bolts at the top and bottom of each column. Base height is adjusted by hand crank with retractable handle. Base adjustment range without top is 26" to 43-3/4". **Note:** Optional casters add 2" to the starting height of the adjustment range.

**Modesty Panels:** Modesty panels are 3/4" thick particleboard construction with .050" high-pressure laminate front and back surface with a 3mm PVC edgeband. Square corners on banded tops have a 1/8" radius. Modesty panel is fastened to underside of work surface with two steel brackets. Modesty panel height is 11".



mediatechnologies contract

cs-porterdesk-200908

892 Industrial Park Drive  
Shelby, MI 49455  
P: 231.861.2194 | F: 231.861.6678  
[www.mtcontract.com](http://www.mtcontract.com)  
[sales@mediatechnologies.com](mailto:sales@mediatechnologies.com)

PURE MICHIGAN®