FULL TIME OTTABLES Occasional Tables



mt,contract

36"DIA X 18"H

FTDT-36-5C

FULL TIME OTTABLES



FULL TIME OTTABLES

- Upholstered 1" thick assembled wood frame is topped with a 1" thick high pressure laminate work surface.
- Work surface is 18" high with 3mm PVC edges.
- Equipped with steel Duo legs with leveling glides.
- · Casters are optional.
- Mates well with Full Time Ottomans!

ROUND STANDARD SIZES

MODEL	DIA.	HEIGHT"
FTDT-20	20	18
FTDT-36	36	18
FTDT-51	51	18

CURVE STANDARD SIZES

MODEL	CURVE	RETURNS	HEIGHT
FTCT-60	60°	24	18

SQUARE STANDARD SIZES

MODEL	WIDTH"	HEIGHT"
FTST-2424	24	18
FTST-3636	36	18

RECTANGLE STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
FTRT-1836	18	36	18
FTRT-2436	24	36	18
FTRT-2448	24	48	18



892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 | F: 231.861.6678 www.mtcontract.com sales@mediatechnologies.com

To Order, Choose Finish Selections & Options

Upholstery: Choose upholstery.

Work surface: Choose a high pressure laminate.

Edges: Choose from our selection of PVC edges.

Steel Legs: Choose from our powder coat selections.

See **MTContracts'** Finish choices at: https://www.mtcontract.com/resources/finishes View our fabric choices at https://www.mtcontract.com/resources/fabrics



Connectivity available in workurface only.

General Specifications

Work surface: Work surfaces are 1" thick, with a 7/8" particleboard core, .050" high-pressure laminate top and a .030 or thicker phenolic backer. Edge is 1/8 PVC. Work surface shapes match the base shapes and are available in round, square, rectangle and 30° curve shapes.

Base: Upholstered base fabricated in round, square, rectangle and 60° curve shapes. Interior construction consists of a structural wood frame wrapped with $\frac{1}{2}$ " thick, 2.3# density foam on the sides with a Dacron slip cover.

Leg Assemblies: Each leg is a weldment fabricated from 5/16" plate steel with a square mounting plate and curved vertical member. The bottom of each leg is fitted with a threaded weld nut and 1-7/8" black leveling glide. Powder coat finish. Four 75mm diameter casters can be substituted for legs at no charge. (FTD-20 uses (5) 50mm diameter casters.)

cs-fulltime_ottables-211020

