GROOTABLE

Tables



GRT-C3060-29 30"D X 60"W X 29"H





GROOTABLE MOUNTED BASE TABLE

- High-pressure laminate work surface with 0.030" phenolic backer. Edges are 3mm PVC.
- Welded and bolted column base is 3" diameter powder coated 16 gauge steel tubing.
- Top mounting plate is 6" x 9".
- Floor mounting plate is 5-1/2" x 7-1/4" x 1/4" steel plate with a 2-1/2" diameter wire access hole. Molded plastic cover with black finish hides mounting screws in floor.
- *Floor mounting hardware not included.





GROOTABLE RECTANGULAR STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
GRT-C2436-	24	36	29
GRT-C2448-	24	48	29
GRT-C2460-	24	60	29
GRT-C2472-	24	72	29
GRT-C3036-	30	36	29
GRT-C3048-	30	48	29
GRT-C3060-	30	60	29
GRT-C3072-	30	72	29



To Order, Choose Finish Selections & Options

Work surface: Choose your high pressure laminate and PVC edge band colors.

Legs: Standard powder coat is black unless specified otherwise.

See MTContract's finish selections at https://www.mtcontract.com/resources/finishes

- POWER/CONNECTIVITY
- 2 power/2 active USB
- 1 open port 72" long cord



General Specifications

Table Top: Table tops are 1-1/4" thick, three-ply 45# particleboard construction with .050" high-pressure laminate top surface and a .030" phenolic backer. Square corners on banded tops have a 1/8" radius. Edges are 3mm PVC.

Mounted Column Base: 16 gauge powder coated steel tube, 3" column with $6" \times 9" \times 1/4"$ steel top mounting plate. Welded floor mounting plate is 5-1/2" x 7-1/4" x 1/4" steel plate with a 2-1/2" diameter wire access hole. Molded plastic cover with black finish hides mounting screws in floor.

Customer to provide (4) floor anchors per base. 5/16" anchors required in cement. 3/8" toggles required in wood.

Connectivity wiring can be routed through the column tube or externally through the use of an optional raceway.

grootable_cs_200909

