

# CHEESEWALL

---

## Tables



CZW-6078L

1"Thick x 78"W x 60"H

# CHEESEWALL



CZW-6078L  
"Swiss" Cheesewall  
With observation holes



CMW-6078L  
"American" Cheesewall  
Without observation holes

## CHEESEWALL

- 1" thick curved high-pressure laminate privacy wall.
- Freestanding and mobile units available.
- Available with 7 observation ports (CZW-6078L) or without ports (CMW-6078L).
- Configure as many walls as needed to define your space.
- Each wall is held upright with (3) 8-1/2"L steel feet fitted with adjustable glides.
- Edges and port hole edges (if applicable) are painted.
- Casters are optional.



Swiss Cheese Wall shown with Orbit Lap Top Table, Full Time Curve Ottomans, Rockford pick table, Hannah Mobile Chair and Smile Chair.

### General Specifications

Screen: The curved screen shall be a 31/32" construction of 3 ply Bendy Luan with .050" high-pressure laminate faces. The screen edges shall be painted and formed into a 42-7/16" radius curve. The curved screen shall be 60" high and 78-5/8" wide. Mobile version shall be 63" overall height.

Model CZW shall have (7) 8" diameter holes in the screen. The hole centers shall be located as follows: (1) hole located along the center line, 13-1/2" from the top edge; (1) hole located 14-3/8" right of the center line, 25-5/16" from the top edge; (2) holes located 23-1/8" right of the center line, (1) hole 10-1/2" from the top edge and (1) hole 38-14" from the top edge. (1) hole located 14-3/8" left of

### To Order, Choose Finish Selections & Options

**Base:** Select HPL for wall surface. Contact factory for paint selection.

**Feet:** Select powder coat.

See **MTContract's** finish choices at <https://www.mtcontract.com/resources/finishes>

### OPTIONS



Locking Casters



Multiple Cheesewall Configuration

### CHEESEWALL (FOOTPRINT)

MODEL	DEPTH"	WIDTH"	HEIGHT"
CMW-6078L	28	78	60
CZW-6078L	28	78	60

the center line, 25-5/16" from the top edge; (2) holes located 23-1/8" left of the center line, (1) hole 10-1/2" from the top edge and (1) hole 38-14" from the top edge. Inside edges of the holes shall be painted.

Feet: Foot assemblies shall be 1/4" powder coated steel "L" brackets with reinforcement gusset. Each of (6) 8-1/2" long assemblies shall have a weldnut on the bottom of the bracket that accepts a standard adjustable glide or caster. Foot assemblies shall bolt through the screen at three pre-drilled positions at the bottom of the screen. Foot assemblies shall be attached using (6) 30mm connector bolts and 1/4-20 connector nuts.



892 Industrial Park Drive  
Shelby, MI 49455  
P: 231.861.2194 | F: 231.861.6678  
[www.mtcontract.com](http://www.mtcontract.com)  
[sales@mediatechnologies.com](mailto:sales@mediatechnologies.com)

cs-cheesewall-200910

PURE MICHIGAN®