



WINGMAN





WINGMAN DESK

- Wingman Desks are available with either box and file drawers or a storage cabinet.
- High-pressure laminate work surfaces.
- Cabinet available in thermally fused laminate or high-pressure laminate.
- Storage cabinet, box and file drawers are available to be positioned on user's left or right.
- Modesty panel and casters are standard.
- Wire management grommet is **standard.**
- Vented steel front panel is standard.

PVC

· Customize with your organization's logo.



WINGMAN DESK BOX AND FILE STANDARD SIZES

Wood

MODEL	DEPTH"	WIDTH"	WORK SURFACE HEIGHT	CABINET HEIGHT"	
		BELL SHAPE WORKSURFACE			
WMBL3366-B	32.5	65.5	29.25	42	
		BEAN S	SHAPE WORK	KSURFACE	
WMBN - 3366-B	32.5	65.5	29.25	42	

WINGMAN DESK STORAGE CABINET STANDARD SIZES

MODEL	DEPTH"	WIDTH"	WORK SURFACE HEIGHT	CABINET HEIGHT"
		BELL SH	IAPE WORK	SURFACE
WMBL3366_29-C	32.5	65.5	29.25	42
		BEAN SH	IAPE WORK	SURFACE
WMBN3366_29-C	32.5	65.5	29.25	42

To Order, Choose Finish Selections & Options

Cabinet Choose from our many high-pressure laminate or Melamine box finishes.

Edges: Choose from our PVC Choices.

Table Top: Choose a high-pressure laminate finish for a bell or bean shaped work surface.

Frame: Choose from our many powder coat options.

See MTContracts' Finish selections at https://www.mtcontract.com/resources/finishes





Vented Storage Cabinet



Box and File Drawers



CASTERS

General Specifications

Cabinet: 42" high cabinet is constructed with 3/4" thick engineered wood with either thermally fused laminate or high pressure laminate box finish and 3mm PVC edges. Cabinet worksurface is 1-1/4" thick, three- ply particleboard with .050" high-pressure laminate top surface and .030" phenolic backer. Edge type is PVC (C), 2 Grommets are provided. One located in the worksurface and one located in the cabinet wall adjacent to the desk worksurface.

Box and File Drawer: model receives one open storage area, one box and one file drawer each with full extension 100# ball bearing drawer slide. Cabinet model receives one open storage area and one locking cabinet.

Cabinet Frame: Steel frame is 11 gauge 1-1/4" square steel tubing. Frame assembly is attached to cabinet using wood screws. Mobile units use casters that attach via threaded inserts on underside of the steel frame assembly.

Work Surface: Table tops are 1" thick, three-ply particleboard with .050" high-pressure laminate top surface and .030" phenolic backer. Edge type is PVC (C). Corners on rectilinear tops are square with a 1/8" radius. Tops are available in Bell and Bean shapes.

Desk Leg Assembly: Legs are 7/8" x 1-1/4", 16-gauge oval tubing. The two legs are spaced and angled outward, with a 3/8" steel rod tying the two legs together. The legs are welded to a 3/16" thick steel top plate. The bottom of each leg is capped with a 1/4" plate and bored and tapped to allow the attachment of a 60mm star caster with brake. Tables are fitted with a matching laminate modesty panel.



cs-wingman-181011



