HANNIBAL

Tech Carts & Lecterns





mt contract

HANNIBAL







User side HP-E2824O-4C*



Interior Cabinet HP-E2824O-4C*

HANNIBAL LECTERN

- Mobile lectern features a high pressure laminate work surface and veneer vertical panels.
- Double front veneer cabinet doors with decorative metal accent and interior shelves.
- · Pencil and paper stops.
- Locking casters for mobility.
- · Vertical chase for wire management.
- 6P (six AC outlet) power strip included.
- Option to add light and/or microphone.







E 3mm Wood





HANNIBAL STANDARD SIZES

MODEL	DEPTH"	WIDTH"	HEIGHT"
HP-E2824	24	28	42

General Specifications

Table Top: Tops are 11/4" thick, three ply 45# particle board construction with .050" high pressure laminate top surface and a .030" phenolic backer Edge is 3mm wood with a 1/8" radius top and bottom. Work surface includes a cleat located 2-3/32" from the bottom edge.

Case Construction: Main cabinet modules are constructed of 3/4" thick three ply particleboard with plain slided "A" grade sequenced wood veneer faces throughout, with exception of base which is 1" thick. Cabinets are assembled using glue and dowel joinery.

Cupboard Door: Doors are constructed of 3/4" thick, three ply particleboard with plain sliced "A" grade wood veneer faces and edged on all sides with 1.5mm solid wood. Door hardware includes concealed hinges, fully adjustable in all 3 axes and decorative metal accent strip.

To Order, Choose Finish Selections & Options

Work Surface: Choose from our selection of high pressure laminates.

Cabinet: Choose from our selection of wood veneers.

Edges: Choose your PVC edgeband for high pressure laminate and melamine, choose a wood edge for veneer cabinets.

See MTContract's finish choices at https://www.mtcontract.com/resources/finishes

ACCESSORIES (INCLUDED)



ACCESSORIES (OPTIONAL)





*Shown with optional microphone.

Adjustable Shelves: Adjustable shelves are 3/4" thick three ply engineered wood with "A" grade wood veneer faces. The exposed edges are edged with 1.5mm solid wood. Shelves are adjustable on 32mm increments.

Base Frame Weldment: Base Frame is a powder coated weldment of two 1-1/4" square, 23-1/8"" wide 14-gauge steel tubes and two 3/8" end frames each with two 3/8" diameter steel bar end caps. Each end cap is drilled and tapped to accept a 60mm locking swivel caster with 3/8"-16 x 1" stem.



cs-hannibal-220325

892 Industrial Park Drive Shelby, MI 49455 P: 231.861.2194 | F: 231.861.6678 www.mtcontract.com sales@mediatechnologies.com

